


Helios 12W Par Lamp

Technical Data Sheet





Constant Brightness. Instantaneous (Zero Warm up).

❖ Longer Life - 50,000+ hours , Low Maintenance

* Easy Installation, make a cut out and push it in.

❖ Cool White, Warm White, Green, Blue, Red, Yellow colors

❖ View angle: 120°. Great uniform color appearance.

❖ Meets IS 3646 (Part 1):1992 Standard

Low voltage 12V/24V DC operated Lamps available.

No IR & UV radiation. RoHs compliant.

Meets IEC safety standards.

Application:

- Ideal for Residential use, Bed Rooms, Bath Rooms, Kitchen and wherever incandescent is in use.
- Huge benefits to use it in Hotels, shops, restaurants, cinema theaters, libraries, schools as long operational hours leads to short pay-back time.
- Inaccessible locations such as high raise ceilings, reception halls, display rooms, chandeliers, no need to replace.

TECHNICAL SPECIFICATIONS

Operating Voltage 80 - 270V AC/DC

Power Consumption 12W (Incl of Driver Losses)

LED Make Nichia / CREE

Color Temperature (CCT) 3000K(WW), 4500K(NW), 6500K(CW)

Color Rendering Index (CRI) (Ra) > 75 LED Efficacy 110 - 140 lm/W

Led Efficacy 110 - 140 lm/W Luminous flux 960-1320 Lumens

Beam Angle 120 Deg

Expected Life Time > 50,000 Hours

Material Aluminum / Poly Carbonate Lens

Cut Out Size Varies by Model Lens Poly Carbonate Lens

Additional Colors Cool White, Warm White, Red,

Blue, Green, Yellow

Working Temperature(°C) -20 to +45


Country of Origin India

Safety Standards Confirms to IS and IEC Safety

Specifications

HELIOS LED LIGHTRONICS (P) LTD TS 69, SIDCO Industrial Estate, Ekkaduthangal Chennai - 600 032 India 44-42611200 7299924902/6

email: <u>marketing@heliosledlightronics.com</u> www.heliosledlightronics.com



Lux Level - 10ft x 10ft Clean Room at 8ft mounting height

